

Technical specifications	USH 150 Soft	USH 35 E Soft & Container	USH 520 Soft & Container	USH 52S Soft	USH 600 Soft
Aircraft Maximum Takeoff Weight (MTOW)	150 kg	350 kg	473 525 kg	500/525 kg	600 kg
Allowed never exceed speed for use (VNE)	140 km/h	240 km/h	230 180 km/h	290/260 km/h	300 km/h
Minimum safe deployment altitude at VNE and MTOW	70 m	100 m	80 m	80 m	150 m
Rate of descent	7,5 m/s	7,5 m/s	7,5 m/s	7,5 m/s	7,5 m/s
Total time of full canopy opening at VNE and MTOW	3 sec	3 sec	3,5 sec	5 sec	6,5 sec
Canopy area	40 m2	63 m2	105 m2	105 m2	107 m2
Ballistic deployment device	UPI-PFE 200	UPI-PFE 200	UPI-PFE 400	UPI-PFE 400	UPI-PFE 400
Parachute weight					
Container with rocket	ND	ND	12,1 kg	ND	ND
Soft Pack	4,7 kg	7,1 kg	10,8 kg	12 kg	12,4 kg
Dimensions					
Container	ND	420 ou 450 mm 195 ou 185 ø mm	560 510 mm 195 ø mm	ND	ND
Soft Pack		Available dimensions	Available dimensions	Available dimensions	Available dimensions
B1 (A x B x C)		115 x 160 x 360 mm	135 x 240 x 280 mm	145 x 260 x 350 mm	145 x 260 x 400 mm
B2 (A x B x C)				145 x 260 x 450 mm	150 x 230 x 420 mm
Service life	24 ans	24 ans	24 ans	24 ans	24 ans
Repack interval	6 ans	6 ans	6 ans	6 ans	6 ans
Recommended retail price (excluding VAT)					
SOFT PACK	2.368,00 €	3.168,00 €	3.904,00 €	4.078,00 €	4.350,00 €
Container	ND	3.264,00 €	3.995,00 €	ND	ND

Options prices excluding VAT	
USH rescue system repack every 6 years	1.165,00 €
Strap for USH Parachute (price per meter)	60,00 €
Mounting bracket for USH container rescue system	105,60 €
Rescue system delivery	included
Assistance with rescue system installation/removal	on request



SOFT PACK	Container
	